



CV4-FLO² and CV4 Max-FLO²

Product Information: CV4 is excited to offer our power sports customer the FLO² and Max-FLO² which are the newest addition to our expanding product line. These air filters are high flow, dual stage, and have been flame laminated to ensure consistent air flow with maximum durability. All of the FLO² filters are manufactured using only premium materials to withstand all forms of oils, cleaners, and fuels. The new CV4 Max-FLO² filter is specifically designed to eliminate the restrictive stock set up cage-screen and air cleaner combination by replacing it with a custom made cage and a high flow flame resistant filter. The air filters have been pre-oiled with No-Toil brand filter oil due to its proven ability to increase air flow. The molecular structure of the No-Toil oil allows for equal or better debris collection over the petroleum competition. The No-Toil oils and cleaners are completely bio-degradable making them environmentally friendly products.

Installation instructions for FLO² Filter: Clean the air box prior to removing the air filter. Then carefully remove the existing stock filter to ensure no debris falls into the intake boot and remove the stock cage. Next install the pre-oiled CV4 FLO² filter onto the stock cage and reinstall on the vehicle. Replace all covers and tighten any related fasteners to ensure a tight fit to the intake boot. Riders that encounter extremely dusty conditions may want to use the No-Toil Grease to ensure a positive seal around the intake boot.

Installation instructions for Max-FLO² Filter: Clean the air box prior to removing the air filter. Carefully remove the existing stock filter to ensure no debris falls into the intake boot. Your new Max-FLO² kit replaces the stock cage and filter. Install the pre-oiled CV4 filter and cage on the vehicle. Next, replace all covers and tighten any related fasteners to ensure a tight fit to the intake boot. Riders that encounter extremely dusty conditions may want to use the No-Toil Grease to ensure a positive seal around the intake boot.

Cleaning Instructions for the filter: In order to clean your air filter you need the No-Toil filter cleaner and warm water. Wash the filter thoroughly in the solution and rinse with warm water. Repeat if necessary to remove any remaining oil or debris. Make sure the filter is dry prior to re-oiling the filter. Next, simply reapply the No-Toil, Non-Toxic, Bio-Degradable air filter oil to the filter until uniform oil absorption is achieved then follow the installation instructions above that are applicable to your FLO² or Max-FLO² filter.